

# Sonesse® ULTRA 50 RS485 Star Head Motors

506A2 1002566



Somfy  
DESIGNED FOR  
SILENCE



A new generation of intelligent motors that are controlled and monitored via Somfy Digital Network™ (SDN) solutions and animeo® IP total solar management system.

## Technical Features


Voltage Supply	120V AC, 60Hz
Index Protection Rating	IP 31 (interior and exterior use)
Limit Switch Type	Electronic
Limit Switch Capacity	300 Turns
Temperature Working Range	32°F to 140°F (0°C to 60°C) (interior use only)
Insulation Class	Class 1 for 120V AC
Wiring	Parallel wiring allowed in accordance with NEC and local electrical codes.

## Certifications




## Type of power cable

RTS 120V AC / 60Hz  
3-conductor SJTW cable



## Dimensions

L1	33.0 in. (838 mm)
L2	32.5 in. (825 mm)
L3	33.6 in. (853 mm)
SJTW Power Cable Length	9.8 ft. (3 mm)
Data Cable (must be ordered separately)	Customizable and available in various lengths



Optional 3C cables available in varying lengths with NEMA plug, Fast Connector and open leads.

## Specifications

Torque	4 Nm
Minimum Torque*	0.4 Nm
Nominal Voltage	24V DC
Rated Current	1.5A
Speed range	Adjustable: 10-25 rpm
Thermal protection	5 minutes
Sound Level***	≤38 dBA

### \*\*\*Sound level:

According to standards ISO 3741 NF 31022 in dBA ref 1pW at nominal torque without end product.


### Fabrication recommendations:

- Operational noise level is reduced when motor, tube, and mechanical accessories are properly adapted to motorized applications.
- Free play must be minimized between the accessories and the end product tube to ensure quiet performance of the motor.
- Interior Tube Diameter (ID) > 47 mm must be respected.
- A motor crown adaptor between motor and end product tube is required to ensure concentric operation of motor.
- 500 Series Drive Stop and Screw (9910004) is recommended to prevent noise and drive wheel separation from motor shaft. This drive stop screw must be tightened with a torque ranging between 1.5Nm and 1.8Nm.
- Somfy Soft Clip Drive Wheel Adaptors (brown in color) are not recommended.




## Data Cable: RJ9/RJ45 (sold separately)

### RJ9 connects to motor



\*Data cable (black) for animeo IP networks  
\*\*Data cable (grey) for powering external modules

### RJ45 connects to network



### 4 Cond. 26AWG modular cable with RJ9 on one end and RJ45 other end - (RTS, Z-Wave®, ZigBee modules)

GREY WITH POWER OUT	2.5 ft. long	#9018545
	8 ft. long	#9018546
	12 ft. long	#9018547
	24 ft. long	#9018548

### 4 Cond. 26AWG modular cable with RJ9 on one end and RJ45 other end - (SDN - animeo IP)

BLACK WITH POWER OUT	2.5 ft. long	#9018541
	8 ft. long	#9018542
	12 ft. long	#9018543
	24 ft. long	#9018544

Visit [somfypro.com/sdn-2-0](https://somfypro.com/sdn-2-0) for complete information on SDN 2.0 Bus Distribution Products.

