

# Sonesse® 40 RTS

404S2 1240380  
 406A2 1240381  
 409R2 1240382



Somfy  
 DESIGNED FOR  
 SILENCE



Radio Technology Somfy®  
 Offers control via  
 Radio Technology  
 Somfy® (RTS)


## Technical Features

<b>Voltage Supply</b>	120V AC, 60Hz
<b>Index Protection Rating</b> (interior use only)	Motor: IP 44 Fast Connector IP55
<b>Limit Switch Type</b>	Electronic RTS
<b>Limit Switch Capacity</b>	200 Turns

<b>Temperature Working Range</b>	32°F to 140°F (0°C to 60°C)
<b>Insulation Class</b>	Class 1 for 120V AC
<b>Antenna</b>	Integrated into power cord. Power cord must be at least 12 inches and must not come in contact with metal.

## Dimensions

	404S2	406A2	409R2
<b>L1</b>	19.96 in. (507 mm)	21.18 in. (538 mm)	21.18 in. (538 mm)
<b>L2</b>	19.00 in. (483 mm)	20.24 in. (514 mm)	20.24 in. (514 mm)
<b>L3</b>	20.5 in. (520 mm)	21.69 in. (551 mm)	21.69 in. (551 mm)
<b>Cable Length</b>	1.6 ft. (.5 m) to Fast Connector		



2 mounting holes for self tapping screws.  
 Dia. 4 mm (cat #100405B) Depth 9 mm spaced 1.14" (29 mm) apart.  
 Self tapping mounting screws are included with each motor.

## Specifications

	404S2	406A2	409R2
<b>Torque</b>	4 Nm	6 Nm	9 Nm
<b>Nominal Voltage</b>	120V / 60Hz		
<b>Rated Current</b>	.95A	1.2A	.98A
<b>Speed</b>	36 rpm	24 rpm	14 rpm
<b>Thermal Protection</b>	4 minutes		
<b>Radio Frequency</b>	433.42 MHz		
<b>*Sound Level</b>	42 dBA	44 dBA	40 dBA

### \*Sound level:

According to standards ISO 3741 NF 31022 in dBA ref 1pW at nominal torque without end product.

### Fabrication recommendations:

- Operational noise level is reduced when motor, tube, and mechanical accessories are properly adapted to motorized applications.
- Free plays have to be minimized between the accessories and the end product tube to ensure quiet performance of the motor.
- Interior Tube Diameter (ID) > or = 38mm must be respected to prevent contact with the basic motor tube.
- 400 Series Drive Stop and Screw (9147894) is recommended to prevent noise and drive wheel separation from motor shaft.

## Certifications




## Type of power cable

### RTS 120V AC / 60Hz

3-Conductor 1.6 ft. SJTW Cable on Motor with Fast Connector



## Extension Cable (sold separately)



### 3 Conductor Fast Connector Extension Cable with NEMA Plug (RTS & RS485)

9021113	1.4 ft.	9021114	4.4 ft.
9021115	8.4 ft.	9020791	10.4 ft.
9020792	18 ft.	9020793	24 ft.

### 3 Conductor Fast Connector Extension Cable with Open Leads or No NEMA

9021157	8.4 ft.
---------	---------

### 3 Conductor Panel Mount Female Fast Connector for direct connection to J-Box

9026398	Panel Mount Female Fast Connector
---------	-----------------------------------

